

MODEL 115 V4

SPECIFICATIONS



Model	a. E115DPL b. E115DSL c. E115DBX d. E115DPX e. E115DCX
Shaft Length mm (in) / Color	a. 508 (20") Blue b. 508 (20") White c. 635 (25") Blue d. / e. 635 (25") White
Weight kg (lbs)	a. / b. 170 (375) c. / d. / e. 177 (390)
Engine Type	Loop Charged V4 60° E-TEC Direct Injection
Bore x Stroke mm (in)	91 x 66 (3.601 x 2.588)
Displacement cc (cu in)	1727 (105.4)
Ignition System	IDI Fast Rise Inductive Ignition
Starter	Electric
Trim Method	FasTrak™ Power Trim and Tilt
Propshaft kilowatts (HP)*	86 kw (115 HP) @ 5750 RPM
Full Throttle Operating Range	5500-6000 RPM
Gear Ratio	a. / b. 2.0:1 c. / d. / e. 2.25:1
Fuel Induction	E-TEC Direct Fuel Injection with stratified low RPM combustion mode
Alternator	Variable Voltage Computer Controlled 133 Amp** / 1800 watt output with Regulator
Cooling	Pressure and Temperature Controlled Water Cooled
Steering	Remote or Accessory Tiller
Limited Warranty	5-year extended limited warranty: Standard 3 + Additional 2***
Emissions Compliance	EPA 2010 CARB 3 STAR European Union



* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMIA) standard 28/83.

** 133 Amp current calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

*** Limited to new Evinrude MY10 and newer engines sold for recreational use only; excluding 65 commercial and 90 commercial models. Special conditions apply. 5 years or 750 hours, whichever occurs first. Contact your authorised BRP dealer, visit brp.com or refer to our Evinrude brochure for full details.