

MODEL 40 SPECIFICATIONS



Model ⁽¹⁾	a. E40DPL b. E40DSL c. E40DTL d. E40DRL
Shaft Length mm (in) / Color	a. / c. / d. 508 (20") Blue b. 508 (20") White
Weight kg (lbs)	a. / b. 109 (240) c. 113 (250) d. 105 (232)
Engine Type	Inline 2-cylinder E-TEC Direct Injection
Bore x Stroke mm (in)	91 x 66 (3.601 x 2.588)
Displacement cc (cu in)	864 (52.7)
Ignition System	IDI Fast Rise Inductive Ignition
Starter	a. / b. / c. Electric d. Rope
Trim Method	a. / b. / c. Power Trim and Tilt d. Manual Tilt
Propshaft kilowatts (HP)*	30 kw (40 HP) @ 5500 RPM
Full Throttle Operating Range	5000-6000 RPM
Gear Ratio	2.67:1
Fuel Induction	E-TEC Direct Fuel Injection with stratified low RPM combustion mode
Alternator	Variable Voltage Computer Controlled 81 Amp** / 1100 watt output with Regulator
Cooling	Pressure and Temperature Controlled Water Cooled
Steering	a. / b. Remote (Tiller Acc.) c. / d. Tiller Standard
Limited Warranty	5-year extended limited warranty: Standard 3 + Additional 2***
Emissions Compliance	EPA 2010 CARB 3 STAR European Union

(1) Selected models authorized to operate on Lake Constance (BSO)

* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMIA) standard 28/83.

** 81 Amp current calculated at 13.5 V. Net dedicated battery charging power output is 25 Amp.

*** Limited to new Evinrude MY10 and newer engines sold for recreational use only; excluding 65 commercial and 90 commercial models. Special conditions apply. 5 years or 750 hours, whichever occurs first. Contact your authorised BRP dealer, visit brp.com or refer to our Evinrude brochure for full details.

©2010 Bombardier Recreational Products Inc. All rights reserved.

®™ Trademark of Bombardier Recreational Products Inc. or its affiliates.

