

MODEL 90 SPECIFICATIONS



Model ⁽¹⁾	a. E90DPL b. E90DSL c. E90DPX
Shaft Length mm (in) / Color	a. 508 (20") Blue b. 508 (20") White c. 635 (25") White
Weight kg (lbs)	a. / b. 145 (320) c. 152 (335)
Engine Type	Inline 3-cylinder E-TEC Direct Injection
Bore x Stroke mm (in)	91 x 66 (3.601 x 2.588)
Displacement cc (cu in)	1296 (79.1)
Ignition System	IDI Fast Rise Inductive Ignition
Starter	Electric
Trim Method	FasTrak™ Power Trim and Tilt
Propshaft kilowatts (HP)*	67 kw (90 HP) @ 5000 RPM
Full Throttle Operating Range	4500-5500 RPM
Gear Ratio	a. / b. 2.0:1 c. 2.25:1
Fuel Induction	E-TEC Direct Fuel Injection with stratified low RPM combustion mode
Alternator	Variable Voltage Computer Controlled 81 Amp** / 1100 watt output with Regulator
Cooling	Pressure and Temperature Controlled Water Cooled
Steering	Remote or Accessory Tiller
Limited Warranty	5-year extended limited warranty: Standard 3 + Additional 2***
Emissions Compliance	EPA 2010 CARB 3 STAR European Union

(1) Selected models authorized to operate on Lake Constance (BSO)

* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMIA) standard 28/83.

** 81 Amp current calculated at 13.5 V. Net dedicated battery charging power output is 25 Amp.

*** Limited to new Evinrude MY10 and newer engines sold for recreational use only; excluding 65 commercial and 90 commercial models. Special conditions apply. 5 years or 750 hours, whichever occurs first. Contact your authorised BRP dealer, visit brp.com or refer to our Evinrude brochure for full details.

©2010 Bombardier Recreational Products Inc. All rights reserved.

®™ Trademark of Bombardier Recreational Products Inc. or its affiliates.

