

# COMPACT & EASY EVINRUDE PORTABLE ENGINES



HAVE A PASSION FOR WATER,  
POWER, FISHING AND FUN?

**E-NATION**

JOIN THE CONVERSATION AT  
[EVINRUDE.COM/ENATION](http://EVINRUDE.COM/ENATION)



**COMPACT.** Many features offered in a small package.

**EASY.** It's all about getting on the water and doing what you want to do.

**EVINRUDE**



# PORTABLES 3.5 - 15 HP

GREAT THINGS COME IN SMALL PACKAGES.

## EVINRUDE ENGINE SPECIFICATIONS



ENGINE TYPE	2-cylinder	2-cylinder	1-cylinder	1-cylinder	1-cylinder
DISPLACEMENT	351 cc (21.41 cu.in.)	209 cc (12.8 cu.in.)	123 cc (7.5 cu.in.)	123 cc (7.5 cu.in.)	85.5 cc (5.2 cu.in.)
BORE X STROKE	61 x 60 mm (2.4 x 2.36 in)	55 x 44 mm (2.17 x 1.73 in)	59 x 45 mm (2.32 x 1.77 in)	59 x 45 mm (2.32 x 1.77 in)	55 x 36 mm (2.17 x 1.42 in)
STARTING	Electric or Manual	Electric or Manual	Manual	Manual	Manual
CONTROL TYPE	Remote Control Tiller Handle	Remote Control or Tiller Handle	Tiller Handle	Tiller Handle	Tiller Handle
GEAR SHIFT	Forward - Neutral - Reverse	Forward - Neutral - Reverse	Forward - Neutral - Reverse	Forward - Neutral - Reverse	Forward - Neutral
GEAR RATIO	2.15:1	2.08:1	2.15:1	2.15:1	2.15:1
PROPELLER SELECTION RANGE	6" - 10"	6.5" - 9.5"	6" - 9"	6" - 9"	4.5" - 7"
TRANSOM HEIGHT	15", 20"	15", 20", 25"	15", 20", 25"	15", 20"	15", 20"
FUEL	Unleaded Gasoline (87 Octane)	Unleaded Gasoline (87 Octane)	Unleaded Gasoline (87 Octane)	Unleaded Gasoline (87 Octane)	Unleaded Gasoline (87 Octane)
OIL TYPE	NMMA Certified FC-W® 4-stroke oil SAE 10W-30/40 (SF, SG, SH, SJ)	NMMA Certified FC-W® 4-stroke oil SAE 10W-30/40 (SF, SG, SH, SJ)	NMMA Certified FC-W® 4-stroke oil SAE 10W-30/40 (SF, SG, SH, SJ)	NMMA Certified FC-W® 4-stroke oil SAE 10W-30/40 (SF, SG, SH, SJ)	NMMA Certified FC-W® 4-stroke oil SAE 10W-30/40 (SF, SG, SH, SJ)
OIL CAPACITY	1 qt. (1000 mL)	27 fl. oz. (800 mL)	15 fl. oz. (450 mL)	15 fl. oz. (450 mL)	10 fl. oz. (300 mL)
FUEL TANK	3.1 US Gal. (12 Lit) Separate Fuel Tank	3.1 US Gal. (12 Lit) Separate Fuel Tank	Internal Fuel Tank Models: 0.29 US Gal. (1.1 Lit) Integral Tank	0.29 US Gal. (1.1 Lit.) Integral Tank	0.26 US Gal. (1 Lit.) Integral Tank
WEIGHT*	114.4 lbs. (52 kg)	81.5 lbs. (37 kg)	55 lbs. (25 kg)	57 lbs. (26 kg)	41 lbs (18.4 kg)
ALTERNATOR OUTPUT	Opt. Accessory: 12V, 145W, 12A (Standard on Electric Start Models)	Opt. Accessory: 12V, 80W, 6A (Standard on Electric Start Models)	Opt. Accessory: 12V, 60W, 5A (Standard on 25" shaft model)	Opt. Accessory: 12V, 60W, 5A	N/A
MAX. RPM RANGE	5,000 - 6,000	5,000 - 6,000	5,000 - 6,000	4,500 - 5,500	5,000 - 6,000
DIGITAL CD IGNITION SYSTEM	S	S	S	S	S
START IN GEAR PROTECTION	S	S	S	S	N/A
THERMOSTAT CONTROLLED COOLING SYSTEM	S	S	S	S	S
THROUGH-THE-PROP EXHAUST	S	S	S	S	N/A
SHALLOW WATER DRIVE	S	S	S	S	N/A
OIL PRESSURE WARNING	S	S	S	S	N/A
POWER TILT	0	0	N/A	N/A	N/A

\* Weight based on lightest model.

BRP US Inc. 10101 Science Drive, Sturtevant, Wisconsin 53177.

©2012 BRP US Inc. (BRP). All rights reserved. ®™ Trademarks of Bombardier Recreational Products Inc. or its affiliates.

**EVINRUDE**®



SEE MORE AT [EVINRUDE.COM](http://EVINRUDE.COM)